



# Key Fob

## The choice for convenient contactless access

Linxens contactless Key Fob is designed for daily use in access control applications such as enterprise security access or hotel access. Its versatile design allows it to fit easily on any standard key ring.

With its small and robust form factor, Linxens Key Fob is almost indestructible and remains unaffected by shocks or regular daily usage. Its TPE housing on the outside and strong inner PC housing turn it into a waterproof and high-impact resistant product. It is available for low-frequency applications and equipped with the Atmel ATA5577 IC. Optional, high-frequency ICs are available on request.

The Key Fob is available in black and blue, custom colors available on request. In addition, customer-specific colors, laser engraving or logo embedding into the casing are available on request.

Dimensions	Thickness	Operating Temperature	Available IC
40.0 x 35.0 mm Hole: Ø 4.0 mm	5.5 mm	-35°C to +80°C	Atmel ATA5577

Additional memory, protocol and product configurations are available upon request.  
Other chip types are available upon request.

RFID

**Overview**

**Operating Frequency**  
• 125 kHz

**Operating Temperature**  
• -35°C to +80°C

**Material**  
• PC / TPE

**International Standards**  
• Encoding: Manchester, FSK2a unlocked (others upon request)

**Application Area**  
• Access Control  
• Hospitality, Leisure & Entertainment

**Options**  
• Laser engraving / embedded logo  
• Customized programming of data  
• Customized color